



Theoretically critical speed Calculations



$$a = 3.8 L$$



$$a = 0.9 L$$

Definitions

$n_{\text{perm.}}$ [min ⁻¹]	maximum permissible speed
a	Installation coefficient
d_2 [mm]	Spindle core diameter
L [mm]	Spindle length between the spindle bearings and spindle ends

Critical speed


In most applications, you need to check tapped spindles at their critical speed.

The critical speed is that speed which causes resonance oscillations of this spindle.


This critical speed depends on the core diameter, the free load-bearing length and on the way the tapped spindle is constructed.

Given a general safety factor of 0.8, the maximum permissible speed can be calculated as follows:

$$n_{\text{perm}} = 392 \cdot \frac{a \cdot d_2}{L^2} 10^5$$



$$b = 4.0 L_1$$



$$b = 2.0 L_1$$

Definitions

F_{perm} [N]	permissible compressive loading
d_2 [mm]	Spindle core diameter
L_1 [mm]	free buckling length, i.e. the maximum distance between the central bearing and the centre of the tapped nut
b	Installation coefficient

Buckling load

The recirculating ball spindle should as far as possible be subjected only to tensile stress. If it is subjected to compressive loads, then the spindle may buckle.

With a safety factor of 3.0 against buckling, the result is

$$F_{\text{zul}} = \frac{34\,000 \cdot b \cdot d_2^4}{L_1^2}$$

Drive dimensioning

Calculations

Drive torque calculation

The required drive torque is made up of

- Load torque M_{load}
- Acceleration torques M_{trans} and M_{rot}
- No load torque $M_{no\ load}$

$$M_A = M_{load} + M_{trans} + M_{rot} + M_{no\ load}$$

Load torque

$$M_{last} = \frac{F_x \cdot p}{2 \cdot \pi \cdot 1000}$$

with feed force $F_x = m \cdot g \cdot \mu$

Translational Acceleration torque

$$M_{trans} = \frac{F_a \cdot p}{2 \cdot \pi \cdot 1000}$$

with feed force $F_a = m \cdot a$

If used vertically, the mass acceleration a must be added to the acceleration due to gravity g ($9.81\ m/s^2$).

Rotational acceleration torque

$$M_{rot} = \frac{J_{sp} \cdot L \cdot n_{max} \cdot a \cdot 2 \cdot \pi}{V_{max} \cdot 60 \cdot 1000}$$

Drive power

$$P = \frac{M_A \cdot n_{max}}{9550}$$


Definitions

M_A	[Nm]	required drive torque
M_{leer}	[Nm]	Torque, resulting from the various loads
M_{leer}	[Nm]	No load torque
M_{rot}	[Nm]	Rotational acceleration torque
M_{trans}	[Nm]	translational acceleration torque
F_x	[N]	Feed force
g	[m/s ²]	Acceleration due to gravity
v_{max}	[m/s]	maximum process speed
m	[kg]	The weight to be conveyed
a	[m/s ²]	Acceleration
p	[mm]	Spindle pitch
P	[kW]	Power
L	[mm]	Length
n_{max}	[rpm]	maximum speed
μ		coefficient of friction
J_{sp}	[kgm ² /m]	Inertial torque of inertia of the spindle per meter
F_a	[N]	Accelerating force

Mechanical specification


Linear unit	LES 4	LES 5	LES 6
Aluminium profile WxH (mm)	75 x 75	225 x 75	150 x 75
Guide weight (kg/m)	6.2	13.8	11.4
Moment of inertia I_x (cm ⁴)	126	299	212
Moment of inertia I_y (cm ⁴)	107	2362	707
Weight with spindle (kg/m)	7.6	15.2	12.8
Guide slides	1x WS 5-70 2x WS 5-70	2x WS 5-70 4x WS 5-70	
Slide weight (kg)	0.34 / 0.68	0.68 / 1.36	
Spindle pitch (mm)	2.5 / 4 / 5 / 10 / 20		
Max. permissible feed force (N)	2626 / 3450 / 3450 / 3150 / 1425		
Repeat accuracy (mm)	± 0.02		
Process path (mm)	L 1 - 150 / L 1 - 280		
Noise level (dBA)	< 85		
Storage temperature range (°C)	0 – 40		
Operating temperature range (°C)	0 – 60 (80)		
Relative air humidity (%)	< 90		

Combination examples




Crossbench

2 × LES 5
PS 4 with VP 2
Slide on slide assembly




Crossbench

2 × LES 5
VP 2 with PS 4




2-axis H-design

2 x LES 4, LES 5, 2 x PS 6, PS 4,
gantry mode




2-axis flatbed configuration

2 x LES 4, LES 5, 2 X PS 2
2 x WV 2, PS 4, gantry mode




2-axis lifting configuration

2 × LES 5, 2 × PS 4
WV 6



2-axis boom configuration


2 × LES 5
2 × PS 4
WV 3



2-axis H-design


LES 5, 2 x LES 6, 2 x WV 7,
2 x PS 12, PS 4, gantry mode

Combination examples




3 axis boom configuration

2 x LES 5, LES 6, WV 3, 2 x PS 4, PS 7




3-axis raised boom configuration

3 x LES 5, WV 3, 2 x PS 4, VP 2




3-axis portal configuration

2 x LES 5, 2 x LES 6, 2 x WV 7,
2 x PS 4, PS 12, gantry mode




3-axis flatbed configuration

2 x LES 4, LES 5, LES 6, 2 x PS 2, 2 x WV 2,
PS 4, PS 7, gantry mode



4-axis portal configuration

3 x LES 5, 2 x LES 6, 2 x WV 7,
3 x PS 4, 2 x PS 12



5-axis flatbed configuration

2 x LES 5 (Z-axis), LES 5 (2 spindle drives)
2 x LES 4, 2 x PS 2, 2 x WV 2,
2 x PS 4 with VP 2

Motor modules

Ordering overview


LES 4/5/6 direct drives	Circular plug	Circular plug with brake	Single axis controller	Multiple axis controller
DC servomotor DC 100	396112 0060	-	MC 1-10	iCU-DC / iPU-DC
Stepper motor MS 200 HT - 2	396058 0060	396058 0260	IT 116 Flash	iMC-P / iMC-S8
EC servomotor EC 60S	396415 0060	396415 0260	MC 1-20	iCU-EC / iPU-EC
EC servomotor EC 60L 48V	396423 0060	-	MC 1-20	iCU-EC / iPU-EC
EC servomotor EC 60L 310V	396423 0070	396423 0270	MC 1-40	iCU-EC / iPU-EC
EC servomotor EC 86L	396466 0070	-	MC 1-40	Switching cabinet
EC servomotor EC 86S	396444 0070	-	MC 1-40	Switching cabinet
Stepper motor MS 300 HT - 2	396082 0060	396082 0260	iMC-S8	iMC-S8
Stepper motor MS 600 HT	396085 0060	-	iMC-S8	iMC-S8
Stepper motor MS 900 HT	396088 0060	-	iMC-S8	iMC-S8
LES 5 integrated	Circular plug	Circular plug with brake	Single axis controller	Multiple axis controller
Stepper motor MS 200 HT - 2	396058 1060	396058 1260	IT 116 Flash	iMC-P / iMC-S8
DC servomotor DC 100	396112 1060	-	MC 1-10	iCU-DC / iPU-DC
EC servomotor EC 60S	396415 1060	396415 1260	MC 1-20	iCU-EC / iPU-EC
EC servomotor EC 60L 48V	396423 1060	-	MC 1-20	iCU-EC / iPU-EC
EC servomotor EC 60L 310V	396423 1070	396423 1270	MC 1-40	Switching cabinet
LES 4/LES 6 side mounting	Circular plug	Circular plug with brake	Single axis controller	Multiple axis controller
Stepper motor MS 200 HT - 2	396058 2060	396058 2260	IT 116 Flash	iMC-P
DC servomotor DC 100	396112 2060	-	MC 1-10	iCU-DC
EC servomotor EC 60S	396415 2060	396415 2260	MC 1-20	iCU-EC
EC servomotor EC 60L 48V	396423 2060	-	MC 1-20	iCU-EC
EC servomotor EC 60L 310V	396423 2070	396423 2270	MC 1-40	iCU-EC

Motor modules

dimensioned drawing

Motor module 1


Part no.	Motor module	Length L
396112 0060	DC 100	185 mm
396058 0360	MS 200 HT-2 with brake	165 mm
396058 0060	MS 200 HT-2 without brake	105 mm



dimensioned drawing

EC 60


Part no.	Motor module	Length L
396415 0260	EC 60S with brake	99 mm
396415 0060	EC 60S without brake	99 mm
396423 0060	EC 60L 48V	120 mm
396423 0070	EC 60L 310V	120 mm



dimensioned drawing

Motor module 2

Part no.	Motor module	Length L
396466 0070	EC 86L	151 mm
396444 0070	EC 86S	126 mm
396085 0060	MS 600HT	96 mm
396088 0060	MS 900 HT	126 mm



Clutch housing

Drive element accessories

Connection options


Direct drive preparation

Connecting options <i>Direct drive</i>	LES 4	LES 6	LES 5	Angular gear fixing 0°	Angular gear fixing 90°
MS 200 HT-2 DC 100 EC 60	Connection via coupling casing 1 <i>short sleeve</i> with adequate shaft coupling			Coupling casing 1 <i>long sleeve</i>	
MS 600 HT MS 900 HT EC 86	Connection via coupling casing 2 <i>short sleeve</i> with adequate shaft coupling			Coupling casing 2 <i>long sleeve</i>	
Angular gear fixing 0°	split coupling casing <i>short sleeve</i> with adequate shaft coupling			Connection via transmission shaft set	
Angular gear fixing 90°	split coupling casing <i>short sleeve</i> with adequate shaft coupling				

Ordering overview

Clutch housing


Clutch housing 1



short sleeve
Part no.: 218 100 0001

long sleeve
Part no.: 218 100 0002


Clutch housing 2



short sleeve
Part no.: 218 100 1001

long sleeve
Part no.: 218 100 1002


Split clutch housing



short sleeve
Part no.: 218 100 2001

long sleeve
Part no.: 218 100 2002

Clutches




coupling	Item no.:	d ₁	d ₂
20/30	218 001 5060	5,0	6,0
	218 001 9999	from 4 to 7 mm	
30/40	218 002 6380	6,35	8,0
	218 002 8080	8,0	8,0
	218 002 9999	from 6 to 13 mm	
40/60	218 003 9580	9,52	8,0
	218 003 9999	from 8 to 18 mm	

Clutch housing

Drive element accessories

dimensioned drawing


Coupling casing 1



*) Measures refer to the dimensions with long sleeves
 d1 = engine shaft diameter 6.35/8/9 mm
 Suitable shaft coupling WK 40/60 on page 2-68 (not included in scope of delivery)

dimensioned drawing


Coupling casing 2



*) Measures refer to the dimensions with long sleeves
 d1 = engine shaft diameter 6.35/8/9 mm
 Suitable shaft coupling WK 40/60 on page 2-68 (not included in scope of delivery)

dimensioned drawing

split coupling casing




*) Measures refer to the dimensions with long sleeves
 Suitable shaft coupling WK 40/60 on page 2-68 (not included in scope of delivery)

Motor pin assignments

Pin assignment for stepper motors

Motor connection



View of pin insert at the insertion side

M23 12-pin Pin	
1	Motor phase 1A
2	Motor phase 1B
3	Motor phase 2A
4	Motor phase 2B
5	+24V switch
6	+24V brake
7	GND switch
8	GND brake
9	Limit switch 1
10	Limit switch 2
11	---
12	---
Housing - cable shield	

Motor connection




View of pin insert on the socket side

Sub-D 9-pin Pin	
1	Motor phase 1A
2	Motor phase 1B
3	Motor phase 2A
4	Motor phase 2B
5	+24V switch
6	+24V brake
7	Limit switch 2
8	GND brake
9	Limit switch 1
Housing - cable shield	

Pin assignment for DC servo motors with brushes (BDC)

Motor connection




View of pin insert on the socket side

M23 9-pol. (8+1) pin	
1	Motor phase 1 (V+)
2	Motor phase 1 (V-)
3	Motor phase 1 (V+)*
4	Motor phase 1 (V-)*
5	+24V brake
6	GND brake
7	---
8	---
9	Earthing lead
Housing - cable shield	

* Part motor phase connection also by means of 2 wires.

Encoder connection




View of pin insert on the socket side

Sub-D 15-pin Pin	
1	---
2	+5V encoder
3	Encoder track/Z
4	Encoder track/B
5	Encoder track/A
6	+24V switch
7	Limit switch 1
8	GND switch
9	---
10	GND encoder
11	Encoder track Z
12	Encoder track B
13	Encoder track A
14	Reference switch
15	Limit switch 2
Housing - cable shield	

Pin assignment for brushless EC servo motors (BLDC) 48V

Motor connection



View of pin insert on the socket side

M23 9-pol. (8+1) pin	
1	Motor phase U
2	Motor phase V
3	Motor phase W
4	---
5	+24V brake
6	GND brake
7	---
8	---
9	Earthing lead
Housing - cable shield	

Encoder connection




View of pin insert on the socket side

Sub-D 15-pin Pin	
1	Hall signal A
2	+5V encoder/Hall
3	Encoder track/Z
4	Encoder track/B
5	Encoder track/A
6	+24V switch
7	Limit switch 1
8	GND switch
9	Hall signal B
10	GND encoder
11	Encoder track Z
12	Encoder track B
13	Encoder track A
14	Hall signal C
15	Limit switch 2
Housing - cable shield	

Motor leads

Pin assignment for brushless EC servomotors (BLDC) 310V


Motor connection



View of pin insert at the insertion side

M23 9-pol. (4+3+1) pin	
1	Motor phase U
PE	Earthing lead
3	Motor phase W
4	Motor phase V
A	+24V brake
B	GND brake
C	Temp +
D	Temp -
Housing - cable shield	

Encoder connection



View of pin insert at the insertion side

Sub-D 15-pin Pin	
1	Hall signal A
2	+5V encoder/Hall
3	Encoder track/Z
4	Encoder track/B
5	Encoder track/A
6	+24V switch
7	Limit switch 2
8	GND switch
9	Hall signal B
10	GND encoder
11	Encoder track Z
12	Encoder track B
13	Encoder track A
14	Hall signal C
15	Limit switch 2
Housing - cable shield	

Overview of motor leads for stepper, DC servo and EC motors*

Part number	Description
392750 0500	5-metre stepper motor lead M23 12-pin plug - socket 1:1
392755 0500	5-metre stepper motor lead D-sub 9-pin plug - M23 12-pin socket
392781 0500	5-metre stepper motor lead D-sub 9-pin plug - socket 1:1
392759 0500	5-metre DC/EC servo motor lead M23 9-pin (8 + PE) plug - socket 1:1
392760 0500	5-metre DC/EC servo motor lead M23 9-pin (8+PE) socket - wire end ferrules
392740 0500	5-metre encoder lead D-sub 15-pin plug - socket 1:1
392325 0500	5-metre encoder lead M23 17-pin socket - D-sub 15-pin plug
392305 0500	3-metre EC/AC servo motor lead M23 310V (4+3+PE) socket - wire end ferrules
392307 0500	5-metre EC servo motor lead M23 (4+3+PE) plug - socket 1:1



All listed motor and encoder leads are fit for use with tow chains.

* Different lengths available on request!

Installation kit with angular transmission

Drive element accessories



Installation alternatives



- ① Angular gear
- ② Split coupling casing with shaft coupling WK 40/60
- ③ LES 4, LES 6 or LES 5 (preparation for direct drive)
- ④ Coupling for transmission shaft $\varnothing 25$
- ⑤ Transmission shaft $\varnothing 25$
- ⑥ Pedestal bearing - recommendable from : transmission shaft length of 1,500 mm up

dimensioned drawing

Angular transmission



Ordering overview

Installation kit with angular transmission

for H-design on LES 4/LES 6/LES 5,
0° mounting
Scope of delivery: 2 x ①, 2 x ②, 2 x ④
Part no.: **216150 0001**

for H-design on LES 4/LES 6/LES 5,
90° mounting
Scope of delivery: 2 x ①, 2 x ②, 2 x ④
Part no.: **216150 0002**

Transmission shaft

Hollow shaft $\varnothing 25$ mm \times 4 mm, blank
1000 mm
Part no.: **219001 0125**

Hollow shaft $\varnothing 25$ mm \times 4 mm, blank
2000 mm
Part no.: **219001 0225**

Coupling/stationary bearing

Coupling for transmission shaft
12 to 25 mm adaptor, VE 2 units
Part no.: **218050 0002**


Stationary bearing for transmission shaft
VE 1 unit
Part no.: **896202 5562**

For matching direct drive modules LES 4/5/6 see table on page 2-66

Installation kit with angular transmission


Drive element accessories

Dimensioned drawing and technical specification



Pedestal bearing- to avoid vibrations/to support the transmission shaft (recommendable from a transmission shaft length of 1,500 mm up)	
Transmissible torque	18 Nm
Weight of coupling	0.3 kg
Weight of shaft	0.540 kg/m
Moment of inertia of both couplings	$2.68 \cdot 10^{-4} \text{ kgm}^2$
Moment of inertia of shaft	$8.171 \cdot 10^{-6} \text{ kgm}^2 / 100 \text{ mm}$

Dimensioned drawing - coupling



Part no. **Z18050 000Z**

Slide/crossbench plates

Connectors

Hole diagram, slide plate PS 1


L 125 x W 70 x H 7.7 mm

Mounting on:
LES 4 with 1 x WS 5/70

Part no.: **277001**

Connecting cross 2 x LES 4

Part no.: **277007**




Hole diagram, slide plate PS 2

L 255 x W 70 x H 7.7 mm

Mounting on:
LES 4 with 2 x WS 5/70

Fixing option for:
Angle bracket WV 2 / WV 5

Part no.: **277002**




Hole diagram, slide plate PS 3

L 220 x W 125 x H 7.5 mm

Mounting on:
LES 5 with 2 x WS 5/70

Part no.: **277003**




Hole diagram, slide plate PS 4

L 225 x W 220 x H 7.5 mm

Mounting on: LES 5 with 4 x WS 5/70

Mounting on crossbench: LES 5 with LES 5 (in conjunction with VP 2) Fixing option for: Angle bracket WV 3 / WV 6

Part no.: **277004**




Hole diagram, slide plate PS 6

L 220 x W 125 x H 7.5 mm

Mounting on: LES 4 with 2 x WS 5/70

Mounting on crossbench: LES 4 with LES 5 (in conjunction with PS 3). Fixing option for: LES 4/LES 5

Part no.: **277011**




Hole diagram, slide plate PS 7

L 255 x W 220 x H 7.5 mm

Mounting on: LES 6 with 4 x WS 5/70

Mounting on crossbench: LES 6 with LES 5 (in conjunction with PS 4)

Part no.: **277016**




Slide/crossbench plates

Connectors

Hole diagram, slide plate PS 8

L 125 × W 145 × H 7.7 mm

Mounting on:


LES 6 with 2 × WS 5/70 **Part no.: 277017**

Hole diagram, slide plate PS 9

L 250 × W 145 × H 7.5 mm

Mounting on: LES 6 with 4 × WS 5/70

Fixing option for: Angle bracket WV 7


Part no.: 277018

Hole diagram, slide plate PS 10

L 210 × W 215 × H 7.5 mm

Mounting on: LES 6 with 4 × WS 5/70

Mounting on crossbench: LES 6 with LES 6 (in conjunction with PS 11)


Part no.: 277019

Hole diagram, slide plate PS 11

L 210 × W 215 × H 7.5 mm

Mounting on: LES 6 with 4 × WS 5/70


Mounting on crossbench: LES6 with LES4 (in conjunction with PS10) Fixing option for: LES 6

Part no.: 277020

Hole diagram, slide plate PS 12

L 220 × W 180 × H 7.5 mm

Mounting on: LES 6 with 4 × WS 5/70


Fixing option for: LES 5 **Part no.: 277021**

Hole diagram, connection plate VP 2

L 255 × W 220 × H 7.5 mm

Mounting on: LES 5 with 4 × WS 5/70

Fixing option for: LES 5

Part no.: 277006

T-slot slide plates



Connectors

Hole pattern T-slot plate PT 25 × 250 for LES 4

L 100 x W 75 x H 20 mm

Mounting on: LES 4 with 1 x WS 5/70


Part no.: **277030 0001**



L 200 x W 75 x H 20 mm

Mounting on: LES 4 with 2 x WS 5/70

Part no.: **277030 0002**





Hole pattern T-slot plate PT 25 × 250 for LES 6

L 100 x W 125 x H 20 mm

Mounting on: LES 6 with 2 x WS 5/70

Part no.: **277030 0003**





Hole pattern T-slot plate PT 25 × 250 for LES 5

L 100 x W 250 x H 20 mm


Mounting on: LES 5 with 2 x WS 5/70

Part no.: **277030 0005**



Angle brackets

Angle bracket with clamping surfaces milled flat



WV 1 WV 2 WV 3 WV 6 WV 7 WV 8 WV 19

Angle bracket WV 1

- blank
- Aluminium casting (0.2 kg)
- L71 × W75 × H71

Part no.: **209110 0010**

Angle bracket WV 2

- blank
- Aluminium casting (2.6 kg)
- L221 × W75 × H446

Part no.: **209110 0022**

Angle bracket WV 3

- blank
- Aluminium casting (5.8 kg)
- L221 × W221 × H446

Part no.: **209110 0032**

Angle bracket WV 6

- blank
- Aluminium, welded (13.3 kg)
- L220 × W220 × H670

Part no.: **209110 0060**

Angle bracket WV 7

- blank
- Aluminium, welded (10.8 kg)
- L220 × W145 × H670

Part no.: **209110 0070**

Angle bracket WV 8

- blank
- Aluminium, welded (7.4 kg)
- L222 × W145 × H446

Part no.: **209110 0080**


Angle bracket WV 19

- blank
- Aluminium, welded (2.5 kg)
- L150 × W221 × H300

Part no.: **209110 0190**

Connectors

matching cover plates



Cover plate for WV 2

- Naturally anodised
- Aluminium sheet, weight 0.8 kg

Part no.: **209110 0021**

Cover plate for WV 3

- Naturally anodised
- Aluminium sheet, weight 1.15 kg

Part no.: **209110 0031**

Cover plate for WV 6

- Naturally anodised
- Aluminium sheet, weight 1.8 kg

Part no.: **209110 0061**

Cover plate for WV 7

- Naturally anodised
- Aluminium sheet, weight 1.5 kg

Part no.: **209110 0071**

Cover plate for WV 8

- Naturally anodised
- Aluminium sheet, weight 1 kg

Part no.: **209110 0081**


Angle bracket

Connectors

Hole diagram

Angle bracket WV 1


L 71 x W 75 x H 71 mm



Hole diagram

Angle bracket WV 2


L 221 x W 75 x H 446 mm



Hole diagram

Angle bracket WV 3

L 221 x W 221 x H 446 mm




Angle brackets

Connectors

Hole diagram

Angle bracket WV 6


L 220 x W 220 x H 670 mm



Hole diagram

Angle bracket WV 7


L 220 x W 145 x H 670 mm



Hole diagram

Angle bracket WV 8


L 222 x W 145 x H 446 mm



Hole diagram

Angle bracket WV 19

L 150 x W 221 x H 300 mm




Accessories

Energy guidance chain




Dimensioned drawing Energy guidance chain




Energy guide chain 3

- VE 1 unit at 1 m
- Part no.: **219204 1000**



Connectors for energy chain 3

- with strain relief
- VE 1 kit
- Part no.: **219205 0002**



Tapped strips/sliding nuts




Figure 1

Figure 2

Figure 4

Figure 3

Tapped strips

- M6** (no figure)
- Galvanised
 - Ra 50 mm
 - 3 x VE 1 m piece
 - Part no.: **209011**

Sliding nut

- 2 × M6** (Figure 2)
- Galvanised
 - VE 50 pieces
 - Part no.: **209002 0004**

Special angle sliding nut

- 3 x M6** (Figure 3)
- Galvanised
 - VE 25 pieces
 - Part no.: **209022 0003**

Sliding nut

- M6** (Figure 1)
- Galvanised
 - VE 100 pieces
 - Part no.: **209001 0005**


Angle sliding nut

- 2 × M6** (Figure 4)
- Galvanised
 - VE 25 pieces
 - Part no.: **209021 0003**

Sliding nut

- M5** (no figure)
- Galvanised
 - VE 20 pieces
 - Part no.: **209006 0001**

Attachment kits



Gas pressure spring

Gas strut attachment kit

- Hub 220 mm
- Nominal length 490 mm
- Part no.: **216450 0001**

Gas strut attachment kit


- Stroke 300 mm
- Nominal length 690 mm
- Part no.: **216451 0001**

Limit switch attachment kit for LES 4

- for external limit switches
- Process path reduction by approx. 40 mm
- Part no.: **216460 0001**

Limit switch attachment kit LES 6

- for external limit switches
- Process path reduction by approx. 40 mm
- Part no.: **216460 0003**



External limit switch

Limit switch attachment kit LES 5

- for external limit switches
- Process path reduction by approx. 40 mm
- Part no.: **216460 0002**

Mounting set for sealing air

- for LES4 - LES6
- Part no.: **216460 0006**